

Description

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 1-1/8", NAS1101 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1101318 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-074-6829 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1101-3-18 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.001 Inches Minimum And 1.125 Inches Maximum |
| Fastener Length: | 1.063 Inches Minimum And 1.125 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.306 Inches Minimum And 0.313 Inches Maximum |
| Head Height: | 0.103 Inches Minimum And 0.118 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum |
| Screw Material: | Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1101 Professional/industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1101-3-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.