

Description

NAS1101E00-4 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1101E004
Minimum Qty (MOQ):	10
NSN:	5305-01-432-3918
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1101E00-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.225 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.092 Inches Minimum And 0.096 Inches Maximum
Head Height:	0.029 Inches Minimum And 0.037 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Iron Alloy 660
Screw Surface Treatment:	Passivate Or Chromate And Cadmium
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1101 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1101E00-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.