

Description

NAS1101E02-5 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1101E025
Minimum Qty (MOQ):	25
NSN:	5305-01-117-0993
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1101E02-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.245 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.136 Inches Minimum And 0.140 Inches Maximum
Head Height:	0.044 Inches Minimum And 0.053 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1101 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1101E02-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.