

Description

Fastener Length: 1-1/8", Thread: 4-40, Thread Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1101E0418
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-159-5546
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1101E04-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.013 Inches Minimum And 1.125 Inches Maximum
Fastener Length:	1.063 Inches Minimum And 1.125 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.178 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.059 Inches Minimum And 0.069 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1101 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1101E04-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.