



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N NAS1101E06-14**

## Description

Fastener Length: 7/8", Thread: 6-32, Thread Length: 7/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1101E0614                              |
| Minimum Qty (MOQ):      | 20  |
| NSN:                    | 5305-00-913-7975                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1101E06-14 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 0.782 Inches Minimum And 0.875 Inches Maximum                     |
| <b>Fastener Length:</b>                                     | 0.844 Inches Minimum And 0.875 Inches Maximum                     |
| <b>Head Style:</b>  | Flat Chamfer  |
| <b>Head Diameter:</b>                                       | 0.221 Inches Minimum And 0.226 Inches Maximum                     |
| <b>Head Height:</b>   | 0.074 Inches Minimum And 0.086 Inches Maximum                     |
| <b>Internal Drive Style:</b>                                | Torque Set  |
| <b>Nominal Thread Diameter:</b>                             | 0.138 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 32  |
| <b>Minimum Tensile Strength:</b>                            | 140000 Pounds Per Square Inch                                     |
| <b>Hardness Rating:</b>                                     | 248.0 Brinell Standard Minimum And 321.0 Brinell Standard Maximum |
| <b>Screw Material:</b>                                      | Iron Alloy 660  |
| <b>Screw Material Document And Classification:</b>          | Ams 5735 Assn Std Single Material Response                        |
| <b>Screw Surface Treatment:</b>                             | Passivate   |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response                        |
| <b>Thread Series Designator:</b>                            | Unjc  |
| <b>Specification/standard Data:</b>                         | 80205-nas1101 Professional/industrial Association Standard        |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1101E06-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.