

P/N NAS1101E08-12

Description

NAS1101E08-12 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1101E0812

Minimum Qty (MOQ): 20

NSN: 5305-01-084-5394

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1101E08-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.657 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.265 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.088 Inches Minimum And 0.102 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1101 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1101E08-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1101E08-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1101E08-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1101E08-12 and selecting the quantity of the property of the property