



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N NAS1101E08H10**

## Description

Fastener Length: 5/8", Hole Diameter: 1/32", Thread: 8-32, Thread Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1101E08H10                             |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5305-00-180-4841                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1101E08H10 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 0.532 Inches Minimum And 0.625 Inches Maximum              |
| <b>Fastener Length:</b>                                     | 0.594 Inches Minimum And 0.625 Inches Maximum              |
| <b>Head Style:</b>  | Flat Chamfer   |
| <b>Head Diameter:</b>                                       | 0.265 Inches Minimum And 0.270 Inches Maximum              |
| <b>Head Height:</b>   | 0.088 Inches Minimum And 0.102 Inches Maximum              |
| <b>Hole Diameter:</b>                                       | 0.038 Inches Nominal                                       |
| <b>Internal Drive Style:</b>                                | Torque Set   |
| <b>Nominal Thread Diameter:</b>                             | 0.164 Inches   |
| <b>Hole Quantity:</b>                                       | 2  |
| <b>Thread Quantity Per Inch:</b>                            | 32   |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch                              |
| <b>Screw Material:</b>                                      | Iron Alloy 660   |
| <b>Screw Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response                 |
| <b>Screw Surface Treatment:</b>                             | Passivate  |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response                 |
| <b>Head Hole Configuration Style:</b>                       | Round  |
| <b>Thread Series Designator:</b>                            | Unjc   |
| <b>Specification/standard Data:</b>                         | 80205-nas1101 Professional/industrial Association Standard |

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1101E08H10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.