



Military-Fasteners.com

P/N NAS1101E08H8

Description

Fastener Length: 1/2", Hole Diameter: 1/32", Thread: 8-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1101E08H8
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-044-7109
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1101E08H8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Pan
Head Diameter:	0.265 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.088 Inches Minimum And 0.102 Inches Maximum
Hole Diameter:	0.039 Inches Nominal
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.164 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1101 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1101E08H8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.