

Description

Fastener Length: 0-63/64", Thread: 10-32, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1101E316P
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-237-3854
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1101E3-16P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.907 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.306 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.103 Inches Minimum And 0.118 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Class 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1101 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1101E3-16P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.