

Description

Fastener Length: 1-5/16", Thread: 10-32, Thread Length: 1-5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS1101E321 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-388-9118 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N NAS1101E3-21 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.251 Inches Minimum And 1.313 Inches Maximum |
| Fastener Length: | 1.251 Inches Minimum And 1.313 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.306 Inches Minimum And 0.313 Inches Maximum |
| Head Height: | 0.103 Inches Minimum And 0.118 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams 5737 Assn Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1101 Professional/Industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1101E3-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.