



Military-Fasteners.com

P/N NAS1101E3H34

Description

Fastener Length: 2-7/32", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 2-3/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1101E3H34
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-227-5063



* See page 2 for technical characteristics

P/N NAS1101E3H34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.094 Inches Nominal
Fastener Length:	2.219 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.312 Inches Nominal
Head Height:	0.094 Inches Nominal
Hole Diameter:	0.034 Inches Minimum And 0.042 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Ams5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35,type 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1101E3H34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.