

Description

Fastener Length: 2-7/32", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 2-3/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1101E3H34 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-227-5063 |



P/N NAS1101E3H34 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 2.094 Inches Nominal |
| Fastener Length: | 2.219 Inches Nominal |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.312 Inches Nominal |
| Head Height: | 0.094 Inches Nominal |
| Hole Diameter: | 0.034 Inches Minimum And 0.042 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Steel Corrosion Resisting |
| Screw Material Document And Classification: | Ams5737 Assn Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35,type 2 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1101E3H34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.