

**Description**


Fastener Length: 2-7/32", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 2-3/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1101E3H34
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-227-5063



## P/N NAS1101E3H34 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	2.094 Inches Nominal
<b>Fastener Length:</b>	2.219 Inches Nominal
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.312 Inches Nominal
<b>Head Height:</b>	0.094 Inches Nominal
<b>Hole Diameter:</b>	0.034 Inches Minimum And 0.042 Inches Maximum
<b>Internal Drive Style:</b>	Torque Set
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Material Document And Classification:</b>	Ams5737 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35,type 2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1101E3H34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.