

Description

Fastener Length: 19/32", Thread: 2-56, Thread Length: 17/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS11020210
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-945-2548
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1102-02-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.521 Inches Minimum And 0.557 Inches Maximum
Fastener Length:	0.593 Inches Minimum And 0.625 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.126 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Torque Set
End Item Identification:	F-16 Aircraft;aircraft,intruder A-6e;prowler Ea-6b Aircraft
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1102 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102-02-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.