

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1102049 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-606-1514 |
| Schedule B: | 7318.15.2010 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS1102-04-9 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.562 Inches Nominal |
| Fastener Length: | 0.562 Inches Nominal |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Titanium Alloy Uns R56400 |
| Screw Material Document And Classification: | Ams 4967 Assn Std Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416, Type Ii, Class 1 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102-04-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.