



Military-Fasteners.com

P/N NAS1102-06-32

## Description

Fastener Length: 1-63/64", Thread: 6-32, Thread Length: 1-7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS11020632
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-148-3672
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1102-06-32 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.819 Inches Minimum And 1.881 Inches Maximum
<b>Fastener Length:</b>	1.938 Inches Minimum And 2.000 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.231 Inches Minimum And 0.279 Inches Maximum
<b>Internal Drive Style:</b>	Torque Set
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas1102 Professional/industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102-06-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.