

Description

Fastener Length: 3/8", Thread: 6-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS110206R6                               |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-01-210-2896                          |
| Schedule B:             | 7318.15.2010                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1102-06R6 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 0.225 Inches Minimum And 0.318 Inches Maximum  |
| <b>Fastener Length:</b>                                     | 0.344 Inches Minimum And 0.375 Inches Maximum  |
| <b>Head Style:</b>  | Flat Countersunk   |
| <b>Head Diameter:</b>                                       | 0.267 Inches Minimum And 0.279 Inches Maximum  |
| <b>Internal Drive Style:</b>                                | Torque Set   |
| <b>Nominal Thread Diameter:</b>                             | 0.138 Inches   |
| <b>Thread Quantity Per Inch:</b>                            | 32   |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                                     | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum  |
| <b>Countersink Angle:</b>                                   | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| <b>Screw Material:</b>                                      | Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate   |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response  |
| <b>Special Features:</b>                                    | Internal Drive Ribbed  |
| <b>Thread Series Designator:</b>                            | Unjc   |
| <b>Specification/standard Data:</b>                         | 80205-nas1102 Professional/industrial Association Standard                                   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102-06R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.