

P/N NAS1102-08-22

Description

Fastener Length: 1-3/8", Thread: 8-32, Thread Length: 1-3/8", NAS1102 series screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS11020822

Minimum Qty (MOQ): 25

NSN: 5305-00-915-2543

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1102-08-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.313 Inches Minimum And 1.375 Inches Maximum
Fastener Length:	1.375 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.270 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1102-08-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.