

P/N NAS1102-08-38

Description

Fastener Length: 2-3/8", Thread: 8-32, Thread Length: 2-19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

National Motor Freight:

SKU / Model:	NAS11020838
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-536-6442
Schedule B:	7318.15.6080
ECCN:	9A991

093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1102-08-38 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.151 Inches Minimum And 2.307 Inches Maximum
Fastener Length:	2.281 Inches Minimum And 2.375 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.270 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1102 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1102-08-38 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.