

Description

Fastener Length: 25/64", Thread: 8-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS110208R6
Minimum Qty (MOQ):	25 EA
NSN:	5305-01-043-3420
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1102-08R6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.226 Inches Minimum And 0.318 Inches Maximum
Fastener Length:	0.360 Inches Minimum And 0.390 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.294 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 1 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1219 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102-08R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.