

P/N NAS1102-3-9

Description

Fastener Length: 9/16", Thread: 10-32, Thread Length: 13/32", NAS1102 series screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS110239

Minimum Qty (MOQ): 100

NSN: 5305-00-834-3702

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS1102-3-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.420 Inches Minimum
Fastener Length:	0.531 Inches Minimum And 0.562 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.322 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1102 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1102-3-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.