

Description

Fastener Length: 5/8", Thread: 1/4-28, Thread Length: 5/8", NAS1102 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | NAS1102410 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-778-2647 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1102-4-10 Specifications

| | |
|-------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.554 Inches Minimum And 0.625 Inches Maximum |
| Fastener Length: | 0.625 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.442 Inches Minimum And 0.507 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037 |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102-4-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.