

**Description**

Fastener Length: 1-1/2", Thread: 1/4-28, Thread Length: 1-1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1102424
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-920-0533
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1102-4-24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.417 Inches Minimum And 1.500 Inches Maximum
<b>Fastener Length:</b>	1.500 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.442 Inches Minimum And 0.507 Inches Maximum
<b>Internal Drive Style:</b>	Torque Set
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037
<b>Screw Material Document And Classification:</b>	Mil-s-5000 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Or Mil-s-6098 Mil Spec Single Material Response Or Mil-s-8503 Mil Spec Single Material Response Or Mil-s-5626 Mil Spec Single Material Response Or Ams-6300 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102-4-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.