

P/N NAS1102-6-22

Description

Fastener Length: 1-3/8", Thread: 3/8-24, Thread Length: 1-13/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1102622

Minimum Qty (MOQ): 10 EA

NSN: 5305-01-511-6733

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1102-6-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.153 Inches Minimum And 1.215 Inches Maximum
Fastener Length:	1.313 Inches Minimum And 1.375 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.653 Inches Nominal
Internal Drive Style:	Torque Set
End Item Identification:	1520013558250
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4140 And Steel Comp 4340 And Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response And Mil-s-5000 Mil Spec 2nd Material Response And Mil-s-6049 Mil Spec 3rd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1102-6-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.