

Description

Fastener Length: 3/16", Thread: 2-56, Thread Length: 9/64", flat countersunk head, NAS1102 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1102E023
Minimum Qty (MOQ):	25
NSN:	5305-01-006-8956
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1102E02-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.085 Inches Minimum And 0.152 Inches Maximum
Fastener Length:	0.157 Inches Minimum And 0.188 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.126 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1102 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102E02-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.