

Description

Length: 5/8in., thread: 4-40, flat head, NAS1102 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[NAS1102E0410](#)

| | |
|-------------------------|---|
| SKU / Model: | NAS1102E0410 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-01-010-4364 |
| ECCN: | EAR99 |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |



* See page 2 for technical characteristics

P/N NAS1102E04-10 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.499 Inches Minimum And 0.580 Inches Maximum |
| Fastener Length: | 0.594 Inches Minimum And 0.625 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.177 Inches Minimum And 0.225 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams 5737 Assn Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas1102 Professional/Industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102E04-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.