

**Description**

Length: 7/16", Thread: 4-40, Thread Length: 25/64", NAS1102 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                                     |
|-------------------------|-----------------------------------------------------|
| SKU / Model:            | NAS1102E047                                         |
| Minimum Qty (MOQ):      | 50                                                  |
| NSN:                    | 5305-00-340-4722                                    |
| Schedule B:             | 7318.15.6080                                        |
| ECCN:                   | EAR99                                               |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |



\* See page 2 for technical characteristics

## P/N NAS1102E04-7 Specifications

|                                                             |                                                            |
|-------------------------------------------------------------|------------------------------------------------------------|
| <b>Thread Class:</b>                                        | 3a                                                         |
| <b>Thread Direction:</b>                                    | Right-hand                                                 |
| <b>Thread Length:</b>                                       | 0.312 Inches Minimum And 0.393 Inches Maximum              |
| <b>Fastener Length:</b>                                     | 0.407 Inches Minimum And 0.438 Inches Maximum              |
| <b>Head Style:</b>                                          | Flat Countersunk                                           |
| <b>Head Diameter:</b>                                       | 0.177 Inches Minimum And 0.225 Inches Maximum              |
| <b>Internal Drive Style:</b>                                | Torque Set                                                 |
| <b>Nominal Thread Diameter:</b>                             | 0.112 Inches                                               |
| <b>Thread Quantity Per Inch:</b>                            | 40                                                         |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch                              |
| <b>Countersink Angle:</b>                                   | 99.0 Degrees Minimum And 101.0 Degrees Maximum             |
| <b>Screw Material:</b>                                      | Iron Alloy 660                                             |
| <b>Screw Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response                 |
| <b>Screw Surface Treatment:</b>                             | Passivate                                                  |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response                 |
| <b>Thread Series Designator:</b>                            | Unjc                                                       |
| <b>Specification/standard Data:</b>                         | 80205-nas1102 Professional/Industrial Association Standard |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102E04-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.