

## Description

Fastener Length: 3/8", Thread: 6-32, Thread Length: 9/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1102E06R6
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-196-5561
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1102E06R6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.225 Inches Minimum And 0.287 Inches Maximum
<b>Fastener Length:</b>	0.344 Inches Minimum And 0.375 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.231 Inches Minimum And 0.279 Inches Maximum
<b>Internal Drive Style:</b>	Torque Set
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams5737 Assn Std Single Material Response
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Special Features:</b>	Internal Drive Ribbed
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas1102 Professional/Industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1102E06R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.