

Description

NAS1102E08-15

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1102E0815
Minimum Qty (MOQ):	5
NSN:	5305-01-172-5550
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



NO IMAGE
AVAILABLE

P/N NAS1102E08-15 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.777 Inches Minimum And 0.870 Inches Maximum
Fastener Length:	0.907 Inches Minimum And 0.938 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.270 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Navy Special Project
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1102 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102E08-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.