

Description

Fastener Length: 1/2", Thread: 8-32, Thread Length: 27/64", flat countersunk head, NAS1102 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1102E088P |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-008-5893 |
| Schedule B: | 7318.15.9000 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1102E08-8P Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.339 Inches Minimum And 0.432 Inches Maximum |
| Fastener Length: | 0.469 Inches Minimum And 0.500 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.270 Inches Minimum And 0.332 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams 5737 Assn Std Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas1102 Professional/Industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102E08-8P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.