

Description

Fastener Length: 13/16", Thread: 10-32, Thread Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1102E313
Minimum Qty (MOQ):	30 EA
NSN:	5305-00-538-7042
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1102E3-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.639 Inches Minimum And 0.732 Inches Maximum
Fastener Length:	0.781 Inches Minimum And 0.812 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.322 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1102 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102E3-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.