

Description

Fastener Length: 5/8", Thread: 10-32, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1102E3R10
Minimum Qty (MOQ):	40 EA
NSN:	5305-01-571-4826
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1102E3R10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
End Item Identification:	1430-01-418-4396 Radar Set, Semitrailer Mounted
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Part Name Assigned By Controlling Agency:	Screw, Machine
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Astm A286 Assn Std Single Material Response
Head Surface Treatment:	Passivate Or Cadmium
Screw Surface Treatment:	Passivate Or Cadmium
Head Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Or Qq-p-416 Type Ii Class 2 Fed Spec Single Treatment Response
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Or Qq-p-416 Type Ii Class 2 Fed Spec Single Treatment Response
Special Features:	Internal Drive Offset Cruciform Recess Per Ms14191 With Flat 100 Deg Head
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1102E3R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.