



Military-Fasteners.com

P/N NAS1102E3R10

Description

Fastener Length: 5/8", Thread: 10-32, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1102E3R10
Minimum Qty (MOQ):	40 EA
NSN:	5305-01-571-4826
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1102E3R10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.594 Inches Minimum And 0.625 Inches Maximum
<b>Fastener Length:</b>	0.594 Inches Minimum And 0.625 Inches Maximum
<b>End Item Identification:</b>	1430-01-418-4396 Radar Set, Semitrailer Mounted
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Part Name Assigned By Controlling Agency:</b>	Screw, Machine
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Material Document And Classification:</b>	Astm A286 Assn Std Single Material Response
<b>Head Surface Treatment:</b>	Passivate Or Cadmium
<b>Screw Surface Treatment:</b>	Passivate Or Cadmium
<b>Head Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Or Qq-p-416 Type Ii Class 2 Fed Spec Single Treatment Response
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Or Qq-p-416 Type Ii Class 2 Fed Spec Single Treatment Response
<b>Special Features:</b>	Internal Drive Offset Cruciform Recess Per Ms14191 With Flat 100 Deg Head
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1102E3R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.