

Description

Fastener Length: 7/8", Thread: 10-32, Thread Length: 25/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1102E3R14
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-582-6291
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS1102E3R14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.764 Inches Minimum And 0.795 Inches Maximum
Fastener Length:	0.844 Inches Minimum And 0.875 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.322 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Torque Set
End Item Identification:	1430-01-418-4396 Radar Set, Semitrailer Mounted
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Screw, Machine, Flat 100 Degree Head, Full Thread, Torque Set
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	A286 Per Ams 5737 Assn Std Single Material Response
Head Surface Treatment:	Passivate
Screw Surface Treatment:	Passivate
Head Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1102E3R14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.