

## Description

Fastener Length: 7/8", Thread: 10-32, Thread Length: 25/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1102E3R14
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-582-6291
National Motor Freight:	096640, Screws, Iron Or Steel



## P/N NAS1102E3R14 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.764 Inches Minimum And 0.795 Inches Maximum
<b>Fastener Length:</b>	0.844 Inches Minimum And 0.875 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.322 Inches Minimum And 0.385 Inches Maximum
<b>Internal Drive Style:</b>	Torque Set
<b>End Item Identification:</b>	1430-01-418-4396 Radar Set, Semitrailer Mounted
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Screw, Machine, Flat 100 Degree Head, Full Thread, Torque Set
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Material Document And Classification:</b>	A286 Per Ams 5737 Assn Std Single Material Response
<b>Head Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment:</b>	Passivate
<b>Head Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1102E3R14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.