

Description

Fastener Length: 7/8", Thread: 10-32, Thread Length: 25/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS1102E3R14 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5305-01-582-6291 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N NAS1102E3R14 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.764 Inches Minimum And 0.795 Inches Maximum |
| Fastener Length: | 0.844 Inches Minimum And 0.875 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.322 Inches Minimum And 0.385 Inches Maximum |
| Internal Drive Style: | Torque Set |
| End Item Identification: | 1430-01-418-4396 Radar Set, Semitrailer Mounted |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Part Name Assigned By Controlling Agency: | Screw, Machine, Flat 100 Degree Head, Full Thread, Torque Set |
| Screw Material: | Steel Corrosion Resisting |
| Screw Material Document And Classification: | A286 Per Ams 5737 Assn Std Single Material Response |
| Head Surface Treatment: | Passivate |
| Screw Surface Treatment: | Passivate |
| Head Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1102E3R14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.