



★ FASTENERS

Military-Fasteners.com

P/N NAS1102E4-16

Description

Fastener Length: 0-63/64", Thread: 1/4-28, Thread Length: 57/64", NAS1102 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1102E416
Minimum Qty (MOQ):	25
NSN:	5305-01-010-3680
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1102E4-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.792 Inches Minimum And 0.894 Inches Maximum
Fastener Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.442 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1102 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102E4-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.