

P/N NAS1102E4-6

Description

Torque head, 1/4-28 thread NAS1102 series screw

Note: This is a commercial item your order may not include manufacturer certs.

Order this part online

Additional Information

SKU / Model: NAS1102E46

Minimum Qty (MOQ): 25

NSN: 5305-01-533-7128

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N NAS1102E4-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.228 Inches Minimum And 0.259 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.442 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Torque Set
End Item Identification:	Airbus A310
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1102 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1102E4-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1102E4-6 and selecting the quantity you