

Description

NAS1102E5-16 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1102E516 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-559-7436 |
| ECCN: | EAR99 |



P/N NAS1102E5-16 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.867 Inches Nominal |
| Fastener Length: | 1.000 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.617 Inches Minimum And 0.635 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.312 Inches |
| Thread Quantity Per Inch: | 24 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams 5737 Assn Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102E5-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.