

P/N NAS1102V3-6

Description

Fastener Length: 3/8", Thread: 10-32, Thread Length: 9/32", NAS1102 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1102V36

Minimum Qty (MOQ): 10

NSN: 5305-01-016-4336

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 136500, Metal Noi / Metal Alloys Noi









^{*} See page 2 for technical characteristics

P/N NAS1102V3-6 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.202 Inches Minimum And 0.295 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.322 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Titanium Alloy
Screw Material Document And Classification:	Ams 4928 Assn Std Single Material Response Or Nas 621 Assn Std Single Material Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1102 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1102V3-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1102V3-6 and selecting the quantity you