

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 13/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1102V38
Minimum Qty (MOQ):	10
NSN:	5305-01-015-6333
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



P/N NAS1102V3-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.327 Inches Minimum And 0.420 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.322 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Titanium Alloy Uns R54520
Screw Material Document And Classification:	Nas621,comp 6al-4v Assn Std Single Material Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1102 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1102V3-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.