

Description

NAS1103-2 Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS11032
Minimum Qty (MOQ):	25
NSN:	5306-01-480-1173
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N NAS1103-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Nominal
Fastener Length:	0.401 Inches Nominal
Head Style:	Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum
Grip Diameter:	0.189 Inches Minimum And 0.190 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.125 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	2490 Pounds Per Square Inch
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Asm 6382 Assn Std Single Material Response Overall Or Ams 6415 Assn Std Single Material Response Overall Or Ams 6484 Assn Std Single Material Response Overall Or Ams 6322 Assn Std Single Material Response Overall Or Ams 6325 Assn Std Single Material Response Overall Or Ams 6327 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams-qq-p-416, Type Ii, Calss 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1103-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.