

P/N NAS1103-46

Description

Fastener Length: 3-5/32", Thread: 10-32, Thread Length: 19/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

	SKU / Model:
Minimum Qty (MOQ): 5 EA	Minimum Qty (MOQ):
NSN: 5306-00-461-1650	NSN:
Schedule B: 7318.15.8085	Schedule B:

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1103-46 Specifications

3a
Right-hand
0.251 Inches Minimum And 0.301 Inches Maximum
3.136 Inches Minimum And 3.166 Inches Maximum
Dished Hexagon
0.110 Inches Minimum And 0.125 Inches Maximum
0.367 Inches Minimum And 0.376 Inches Maximum
0.1885 Inches Minimum And 0.1895 Inches Maximum
0.190 Inches
2.865 Inches Minimum And 2.885 Inches Maximum
32
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Unjf
80205-nas1103 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS1103-46 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS1103-46 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS1103-46 and selecting the quantity you want then click "add to cart".