

P/N NAS1104-17

Military-Fasteners.com

Description

NAS1104-17 Shear Bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS110417
Minimum Qty (MOQ):	10
NSN:	5306-00-582-9131
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1104-17 Specifications

Thread Direction:Right-handThread Length:0.316 Inches MinimumFastener Length:1.378 Inches NominalHead Style:Dished HexagonHead Style:0.125 Inches NominalHead Height:0.125 Inches NominalWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumGrip Diameter:0.2485 Inches NominalNominal Thread Diameter:0.250 Inches0.250 Inches0.250 InchesGrip Length:1.062 Inches NominalThread Quantity Per Inch:28Baterial Document And50.00 Rockwell C Mainum Overall And 40.0 Rockwell C Maximum OverallMaterial Streigth:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial Document AndSteel Comp 4140 Overall Or Steel Comp E1340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8745 Overall Or Mils-s6036 Mil Spec 1st Material Response Overall Or Mils-s6039 Mil Spec 3th Material Response Overall Or Mils-s60		
Thread Length:3.16 Inches MinimumFastener Length:1.378 Inches NominalHead Style:Dished HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumOrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesOrip Length:1.052 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:1.060 Inches Guard Inches Maximum Overall And 4.0.0 Rockwell C Maximum OverallMaterial:36.0 Rockwell C Minimum Overall And 4.0.0 Rockwell C Maximum OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8750 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Qep-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Or Mil-s-6049 Mil Spec Stem Material Response OverallClassification:Qep-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Thread Class:	За
Fastener Length:1.378 Inches NominalHead Style:Dished HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumOrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesOrip Length:1.062 Inches NominalThread Quantity Per Inch:28Biomoni Strength:16000 Pounds Per Square InchHardness Rating:6.0. Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8750 Overall Or Mil-s-6098 Mil Spec varlal Or Mil-s-6009 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec Sth Material Response Overal	Thread Direction:	Right-hand
Head Style:Disked HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 Inches0.250 Inches0.250 InchesGrip Length:1.062 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Ov	Thread Length:	0.316 Inches Minimum
Head Height:0.125 Inches NominalWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:0.262 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-604	Fastener Length:	1.378 Inches Nominal
Width Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:1.062 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall Spec Single Treatment Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall Spec Single Treatment Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall Spec Single Treatment Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall Spec Single Treatment Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall Spec Single Treatment Response OverallSurface Treatment:Cadmium Ov	Head Style:	Dished Hexagon
Grip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:1.062 Inches Nominal1.062 Inches Nominal1.062 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mil-s-6503 Mil Spec 3rd MaterialMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6099 Mil Spec 4th Material Response Overall Or Mil-s-6099 Mil	Head Height:	0.125 Inches Nominal
Nominal Thread Diameter:0.250 InchesGrip Length:1.062 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall OrMaterial:Mili-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd MaterialRaterial Document And Classification:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallBurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallBurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallBurface Treatment:Cadmium Overall And Chromate Overall <t< th=""><td>Width Between Flats:</td><td>0.430 Inches Minimum And 0.439 Inches Maximum</td></t<>	Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Length:1.062 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment And Classification:Q-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Thread Quantity Per Inch:28Thread Quantity Per Inch:160000 Pounds Per Square InchMinimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assan std 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Classification:Qu-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn std 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallOcument And Classification:Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Grip Length:	1.062 Inches Nominal
Hardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallOcument And Classification:Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	28
Material:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn std 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallOcument And Classification:Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Ass std 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material Document And Classification:Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Material:	
Surface Treatment Document And Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Classification:	Material Document And Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn
Document And Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Classification: Classification:	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Document And	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unf

How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS1104-17</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.