

P/N NAS1104-35D

Military-Fasteners.com

#### Description

Fastener Length: 2-1/2", Thread: 1/4-28, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

### **Additional Information**

SKU / Model:	NAS110435D
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-822-7227
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS1104-35D Specifications

Thread Class:3aThread Direction:Right-handThread Length:0.316 Inches MinimumFastener Length:2.503 Inches NominalHead Style:Dished HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.430 Inches Minimum And 0.439 Inches Maximum
Thread Length:0.316 Inches MinimumFastener Length:2.503 Inches NominalHead Style:Dished HexagonHead Height:0.125 Inches Nominal
Fastener Length:2.503 Inches NominalHead Style:Dished HexagonHead Height:0.125 Inches Nominal
Head Style: Dished Hexagon   Head Height: 0.125 Inches Nominal
Head Height: 0.125 Inches Nominal
Width Potwoon Elater 0.420 Inches Minimum And 0.420 Inches Maximum
With between Flats: 0.450 Inches Mininum And 0.459 Inches Maximum
Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum
Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole
Nominal Thread Diameter: 0.250 Inches
Grip Length: 2.187 Inches Nominal
Thread Quantity Per Inch: 28
Minimum Tensile Strength: 160000 Pounds Per Square Inch
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Distance From Head Largest   Bearing Surface To Shank Hole   2.387 Inches Nominal First Hole     Center:   Conter:   Conter:   Conter:
Material:     Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740       Overall Or Steel Comp 4037 Overall
Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
Surface Treatment: Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:
Thread Series Designator: Unf

# How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NAS1104-35D</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.