

## **P/N NAS1106-39D**

### **Description**

Fastener Length: 2-53/64", Thread: 3/8-24, Thread Length: 13/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS110639D

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-413-0398

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1106-39D Specifications

Thread Class:	3a
Thread Length:	0.366 Inches Minimum And 0.416 Inches Maximum
Fastener Length:	2.813 Inches Minimum And 2.843 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.683 Inches Minimum First Hole And 2.733 Inches Maximum First Hole
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1106 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1106-39D">https://military-fasteners.com/bolts/machine+bolts/NAS1106-39D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1106-39D">https://military-fasteners.com/bolts/machine+bolts/NAS1106-39D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1106-39D">https://military-fasteners.com/bolts/machine+bolts/NAS1106-39D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1106-39D">https://military-fasteners.com/bolts/machine+bolts/NAS1106-39D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/nas-pi-achine-bolts/NAS1106-39D">https://military-fasteners.com/bolts/nas-pi-achine-bolts/NAS1106-39D</a> and selecting the quantity you want then click "add to cart".