

P/N NAS1121E3

Military-Fasteners.com

Description

Fastener Length: 15/32", Thread Length: 19/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

	C 1	1	21	1 I	E 2	
NA	21	. 1	Ζ.	L-1	E 0)

SKU / Model:	NAS1121E3	
Minimum Qty (MOQ):	10	
NSN:	5305-00-432-5599	
Schedule B:	7318.15.6080	
ECCN:	EAR99	
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)	



P/N NAS1121E3 Specifications

Thread Class:	3a		
Thread Length:	0.251 Inches Minimum And 0.301 Inches Maximum		
Fastener Length:	0.449 Inches Minimum And 0.479 Inches Maximum		
Head Height:	0.074 Inches Minimum And 0.086 Inches Maximum		
Minimum Tensile Strength:	160000 Pounds Per Square Inch		
Surface Finish:	32.0 Microinches Bearing Surface Of Head		
Surface Finish:	32.0 Microinches Grip		
Surface Finish:	32.0 Microinches Threads		
Material:	Iron Alloy 660 Overall		
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall		
Surface Treatment:	Passivate Overall		
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall		

How to Order

Order this close tolerance bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1121E3</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.