



Military-Fasteners.com

P/N NAS1122-15

## Description

Fastener Length: 1-7/32", Thread: 8-32, Thread Length: 19/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS112215                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-01-006-0297                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1122-15 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.251 Inches Minimum And 0.301 Inches Maximum   |
| <b>Fastener Length:</b>                               | 1.199 Inches Minimum And 1.229 Inches Maximum   |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.265 Inches Minimum And 0.270 Inches Maximum   |
| <b>Head Height:</b>                                   | 0.088 Inches Minimum And 0.102 Inches Maximum   |
| <b>Grip Diameter:</b>                                 | 0.1625 Inches Minimum And 0.1635 Inches Maximum   |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)   |
| <b>Nominal Thread Diameter:</b>                       | 0.164 Inches  |
| <b>Grip Length:</b>                                   | 0.928 Inches Minimum And 0.948 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall                                       |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads  |
| <b>Material:</b>                                      | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjc  |
| <b>Specification/standard Data:</b>                   | 80205-nas1122 Professional/industrial Association Standard  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1122-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.