

P/N NAS1123-14

Military-Fasteners.com

#### Description

Fastener Length: 1-5/32", Thread: 12-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

### **Additional Information**

SKU / Model:	NAS112314
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-927-0021
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS1123-14 Specifications

Thread Direction: Right-hand   Thread Length: 0.276 Inches Minimum And 1.166 Inches Maximum   Fastener Length: 1.136 Inches Minimum And 1.166 Inches Maximum   Head Style: Flat Chamfer   Head Diameter: 0.296 Inches Minimum And 0.313 Inches Maximum   Origo Diameter: 0.138 Inches Minimum And 0.189 Inches Maximum   Origo Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum   Internal Drive Style: Offset Cruciform (torque Set)   Nominal Thread Diameter: 0.192 Inches   Origo Length: 0.875 Inches Nominal   Thread Quantity Per Inch: 32   Surface Finish: 32.0 Microinches Searing Surface Of Head   Surface Finish: 32.0 Microinches Grip   Surface Finish: 32.0 Microinches Grip   Surface Finish: 32.0 Microinches Grip   Surface Finish: 32.0 Microinches Threads   Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6009 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Respon		
Thread Length:0.276 Inches MinimumFastener Length:1.136 Inches Minimum And 1.166 Inches MaximumHead Style:Fiat ChamferHead Diameter:0.296 Inches Minimum And 0.313 Inches MaximumHead Height:0.103 Inches Minimum And 0.118 Inches MaximumGrip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumInternal Drive Style:Offset Cruciform (torque Set)Nominal Thread Diameter:0.192 Inches0.192 Inches Minimum And 0.1895 Inches MaximumGrip Length:0.875 Inches NominalThread Quantity Per Inch:3236.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Baering Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Response Overall Or Stel Comp E4340 Overall Or Stel Comp E1350 Overall Or Stel Comp B735 Overall Or Stel Comp B735Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response	Thread Class:	За
Fastener Length: 1.136 Inches Minimum And 1.166 Inches Maximum   Head Style: Flat Chamfer   Head Diameter: 0.296 Inches Minimum And 0.313 Inches Maximum   Head Height: 0.103 Inches Minimum And 0.118 Inches Maximum   Grip Diameter: 0.185 Inches Minimum And 0.1895 Inches Maximum   Internal Drive Style: Offset Cruciform (torque Set)   Nominal Thread Diameter: 0.192 Inches   0.192 Inches Offset Cruciform (torque Set)   Nominal Thread Diameter: 0.192 Inches   0.192 Inches Offset Cruciform (torque Set)   Nominal Thread Diameter: 0.192 Inches   0.192 Inches Set Cruciform (torque Set)   Nominal Thread Diameter: 0.192 Inches   0.192 Inches Set Cruciform (torque Set)   Thread Quantity Per Inch: 32   32.0 Microinches Bearing Surface Of Head Surface Finish:   Surface Finish: 32.0 Microinches Grip   Surface Finish: 32.0 Microinches Grip   Surface Finish: 32.0 Microinches Comp E4340 Overall Or Steel Comp E150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall   Overall Material Response Overall Or Mil-s-6008 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Ov	Thread Direction:	Right-hand
Head Style:Flat ChamferHead Diameter:0.296 Inches Minimu And 0.313 Inches MaximumHead Height:0.103 Inches Minimu And 0.1895 Inches MaximumGrip Diameter:0.1885 Inches Minimu And 0.1895 Inches MaximumInternal Drive Style:Offset Cruciform (torque Set)Nominal Thread Diameter:0.192 Inches0.192 Inches0.192 InchesGrip Length:0.875 Inches NominalThread Quantity Per Inch:32JInimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 3th Material Response Overall Or Mil-s-6039 Mil Spec 4th Material Response Overall Or Mil-s-6039 Mil Spec 5th Material Response Overall Or Mil-s-6039 Mil Spec 3th Material Response Overall Or Mil-s-6039 Mil Spec 3th Material Response Overall Or Mil-s-6039 Mil Spec 3th Material Response Overall Or Mil-s-6039 Mil Spec 4th Material Response Overall Or Mil-s-6039 Mil Spec 5th Material Response Overall Or Mil-s-6039 Mil Spec 3th Material Response Overall Or Mil-s-6039 Mil Spec 4th Material Response Overall Or Mil-s-6039 Mil Spec 5th Material Response Overal	Thread Length:	0.276 Inches Minimum
Head Diameter:0.296 Inches Minimum And 0.313 Inches MaximumHead Height:0.103 Inches Minimum And 0.118 Inches MaximumGrip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumInternal Drive Style:Offset Cruciform (torque Set)Nominal Thread Diameter:0.192 Inches0.875 Inches Nominal0.875 Inches NominalThread Quantity Per Inch:32Minimum Tensile Strength:0.6000 Pounds Per Square Inch0.6000 Pounds Per Square Inch36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Overall Or Steel Comp E4340 Overall Or Steel Comp E4340 Overall Or Steel Comp B735 Overall Or Steel Comp B735Material Document And Classification:Mils-s5626 Mil Spec 1st Material Response Overall Or Mils-s6009 Mil Spec 2nd Material Response Overall Or Mils-s6049 Mil Spec 3rd Material Response Overall Or Mils-s6049 Mil Spec 5th Material Response Overall Or Mils-s6049 Mil Spec 5th Material Response Overall Or Mils-s6049 Mil Spec 5th Material Response Ove	Fastener Length:	1.136 Inches Minimum And 1.166 Inches Maximum
Head Height:0.103 Inches Minimum And 0.118 Inches MaximumGrip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumInternal Drive Style:Offset Cruciform (torque Set)Nominal Thread Diameter:0.192 InchesOnginal Thread Diameter:0.875 Inches NominalThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-803 Mil Spec 3th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6094 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall	Head Style:	Flat Chamfer
Grip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumInternal Drive Style:Offset Cruciform (torque Set)Nominal Thread Diameter:0.192 InchesOrig Length:0.192 Inches NominalThread Quantity Per Inch:3233000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsBaterial I:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mil-s-6038 Mil Spec 3rd Material Response Overall Or Mil-s-6039 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6039 Mil Spec 3rd Material Response Overall O	Head Diameter:	0.296 Inches Minimum And 0.313 Inches Maximum
Internal Drive Style:Offset Cruciform (torque Set)Nominal Thread Diameter:0.192 InchesGrip Length:0.875 Inches NominalThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Pocument AndSteel Comp 140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Mil-s-6039 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall	Head Height:	0.103 Inches Minimum And 0.118 Inches Maximum
Nominal Thread Diameter:0.192 InchesGrip Length:0.875 Inches NominalGrip Length:0.875 Inches NominalThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterialSteel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6009 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall OverallSurface Treatment:Camium Overall	Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Grip Length:0.875 Inches NominalGrip Length:0.875 Inches NominalThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall	Internal Drive Style:	Offset Cruciform (torque Set)
Thread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall	Nominal Thread Diameter:	0.192 Inches
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall	Grip Length:	0.875 Inches Nominal
Hardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall	Thread Quantity Per Inch:	32
Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Surface Treatment Document AndCadmium Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document AndCadmium Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:cadmium OverallSurface Treatment Document And Surface Treatment Document AndHorewallSurface Treatment Document And Surface Treatment Document AndHorewallSurface Treatment Document And Surface Treatment Document AndHorewallSurface Treatment Document And Surface Treatment Document AndHorewall Document And Surface Treatment Document And Surface Treatment Document And	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall	Surface Finish:	32.0 Microinches Grip
Material: Overall   Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd   Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall   Surface Treatment: Cadmium Overall   Surface Treatment Document And Surface Treatment Document And	Surface Finish:	32.0 Microinches Threads
Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall   Surface Treatment Document And Cadmium Overall	Material:	
Surface Treatment Document And		
Surface Treatment Document And	Surface Treatment:	Cadmium Overall
Classification: Qq-p-415,ty 2,cl 3 Fed Spec Single Treatment Response Overall		Qq-p-415,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unjf	Thread Series Designator:	Unjf
Specification/standard Data: 80205-nas1123 Professional/industrial Association Standard	Specification/standard Data:	80205-nas1123 Professional/industrial Association Standard

# How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS1123-14</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.