

Description

Fastener Length: 1-5/16", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS1123E17 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-438-0372 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



* See page 2 for technical characteristics

P/N NAS1123E17 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.276 Inches Nominal |
| Fastener Length: | 1.338 Inches Nominal |
| Head Style: | Flat Fillister |
| Head Diameter: | 0.306 Inches Minimum And 0.313 Inches Maximum |
| Head Height: | 0.103 Inches Minimum And 0.118 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.062 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1123 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1123E17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.